210S

Panel	22'' (55.87 cm) TFT Active Matrix LCD, Super Narrow Bezel, Diagonal Hard Coating (3H), Anti-glare Treatment
Design Line	Standard
Pixel / Dot Pitch	0.282mm x 0.282mm
Viewable Image Size (Diagonal)	
Display Area	477.7mm x 300.1 mm
Brightness	300 cd/m² (typ.)
Contrast Ratio	700:1 (typ) (2000:1 DCR)
Typ. Response Time (tr+tf)	5 ms
Viewing Angle	CR=10: 170/160 Degrees
Compatibility	VESA, XGA, SVGA, VGA, WSXGA. Mac®Equipped With VGA Port.
Scanning Frequency	Horizontal: 30K~83KHz Vertical: 55~75 Hz
Pixel Frequency	165 MHz
Maximum Resolution	1680x1050@60HZ
Recommended Resolution	1680x1050@60HZ
Resolution Supported	640x480@60/75/72Hz, 800x600@/56/60/75/72Hz, 1024x768@60/70/75Hz, 1280x1024@60/75Hz 1400x1050@60HZ 1680x1050@60HZ
Colours	16.7M
Signal Input	Analogue: Video: 0.7Vp-p, RGB analogue, Separate Sync: TTL Level, H/V Sync: Positive / Negative,
Connectors	RGB Signal: 15-pin D-sub Male (Attached) Power: 3-pin Plug (CEE22),
Power Source	Power Input: Universal 100~240VAC, 50/60Hz
Power Consumption	49 Watts (Max)
Plug & Play	DDC2B
EPA ENERGY STAR ®	
User Control	EXIT.Auto Adjust, Left Key, Right Key, Menu Key, On/Off Key
Function	Brightness, Contrast,ECO.Gamma.DCR. Focus, Clock, H/V Position. Colour Temperature (Warm. Normal, sRGB, Coo,User – R,G,B, Y,C,M). Color Boost, Picture Boost , • OSD Options.Special Adjustment
OSD Languages	English/French/German/Spanish/Italian/Portuguese/Russian/ Simplified Chinese
Speaker	N/A
Emissions Standard	
Regulation	UL, CSA, FCC, TUV/GS, CE, ISO 13406-2, Windows®XP Logo
Other Features	VESA Wall Mountable, Kensington Security Slot
Dimensions (WxHxD)	Carton:610x189x515
Weight	Net: 5.81 kgs Gross: 7.85 kgs
Loading Qty w/pallet	20"432pcs 40"912pcs
Warranty	3 Years Parts & Labour

Note: Specifications are subject to change without notice. *Wall mount arm & bracket not included.